

PRODUCT MAINTENANCE GUIDE

Thank you for choosing PALLISIDE® weatherboards as the exterior cladding for your home. Dynex offers a 25-year guarantee for the PALLISIDE® weatherboard system.

To ensure your home continues to look its best, please follow the maintenance instructions below.

- We recommend your weatherboards are washed down annually.
- DO NOT use solvent-based or abrasive-type cleaners with PALLISIDE®. If you have any doubts about the suitability of a specific cleaning agent, please contact the manufacturer of the cleaner, or Dynex, regarding its use with uPVC beforehand.
- Use a wet cloth or soft house brush and warm soapy water to remove surface marks and mould build-up.
- Chlorine-based household cleaners can be used, diluted in accordance with the cleaner manufacturer's instructions regarding use on uPVC.
- Water-blasters can also be used to clean PALLISIDE®, ensuring care is taken around junctions and connections to ensure there is no water penetration behind the exterior cladding.
- All areas where flashings, sealants and penetrations are present should be checked regularly to ensure that their integrity is intact. If any deterioration has occurred, please contact your installer or Dynex for advice.

Please note that the PALLISIDE® guarantee is not subject to the product being kept clean, however incorrect cleaning or maintenance practices may void the guarantee.

Please note over time there may be slight visible chalking or fading of the PALLISIDE® surface. This is not a product defect and can be removed by periodic cleaning with soapy water. This will not affect the long-term durability and weather protection of PALLISIDE®.