

### **SAFETY DATA SHEET**

According to HSNO Hazardous Substances (Safety Data Sheets) Notice 2017

### Section 1. Identification of the material and the supplier

Product: Palliside

Product Use: Lead-free - Unplasticised Polyvinyl Chloride

Restriction of Use: Refer to Section 15

New Zealand Supplier: **Dynex** 

Address: 310-316 Rosebank Road

**Avondale, Auckland** 

Telephone: 0800 4 Dynex (0800 439 639)

Fax No: 0800 737 375

Emergency No: 0800 764 766 (National Poison Centre)

Date of SDS Preparation: 22 June 2020

### Section 2. Hazards Identification

This substance is not hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

## Section 3. Composition / Information on Hazardous Ingredients

D) (C D : (C) (C) (C) (C)	Ingredients	Wt%	CAS NUMBER.
PVC Resin (CH2CHCI) <sub>n</sub> >/0 9002-86-2	PVC Resin (CH2CHCI) <sub>n</sub>	>70	9002-86-2

Functional Additives as required Balance

Stabilisers: Organometallic tins, mixed metal salts and special purpose stabilisers.

Process Aids: Acrylics and Styrene acrylonitriles.

Impact Modifiers: Acrylics and Methacrylate Butadiene Styrenics. Fillers: Metal carbonates (principally calcium, magnesium).

Lubricants: Paraffin waxes, mineral oils, polyethylene, salts of fatty acids and fatty

acid esters and amides.

Pigments: Commercially available pigments based on iron oxide, carbon black,

ultramarines, phthalocyanines, molybdates, quinacridones and other organic and inorganic pigments. In weatherable compounds, titanium

dioxide may be present in concentrations of 10 - 15%.

#### Section 4. First Aid Measures

### Routes of Exposure:

If in Eyes Rinse cautiously with water for 15 minutes. If eye irritation persists: Get

medical advice.

If on Skin Wash with plenty of soap and water. If skin irritation occurs: get medical

advice/attention.

Product Name: Lead-free Rigid PVC SDS Prepared by: Technical Compliance Consultants (NZ) Ltd Date of SDS: 22 June 2020 Tel: 64 9 475 5240 www.techcomp.co.nz

Page 1

If Swallowed Wash out mouth thoroughly with water. Never give anything to the mouth

of an unconscious person. If vomiting occurs, place victim face

downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Seek medical attention if needed.

If Inhaled

Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Apply artificial respiration if not breathing. Get medical advice if breathing becomes difficult.

Most important symptoms and effects, both acute and delayed

Symptoms: None known.

### Section 5. Fire Fighting Measures

Hazard Type	PVC is self-extinguishing and does not support combustion.
Hazards from combustion products	PVC decomposes when burned, evolving hydrogen chloride, carbon monoxide, and other toxic gases. Exposure to combustion products may be fatal and should be avoided.
Suitable Extinguishing media	Chemical Foam, Dry Chemical, CO2
Precautions for firefighters and special protective clothing	When fighting fire, self-contained breathing apparatus and full protective clothing should be worn. Remove source of ignition.
HAZCHEM CODE	None Allocated

#### Section 6. Accidental Release Measures

Wear protective gear as detailed in Section 8. Evacuate non-essential personnel.

Sweep up. Put in a container for disposal. Dispose of in compliance with local and/or national regulations.

### Section 7. Handling and Storage

#### Precautions for safe handling:

- Read label before use.
- Wear protective clothing as detailed in Section 8.

### **Precautions for safe storage:**

- Store locked up.
- · Keep out of reach of children.
- Store away from incompatible materials listed in Section 10.

#### **Section 8** Exposure Controls / Personal Protection

### **WORKPLACE EXPOSURE STANDARDS (provided for guidance only)**

TWA STEL Substance ppm mg/m³ ppm mg/m³

No ingredients have exposure limits

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices NOV 2019 11<sup>TH</sup> EDITION.

Product Name: Lead-free Rigid PVC SDS Prepared by: Technical Compliance Consultants (NZ) Ltd

Date of SDS: 22 June 2020 Tel: 64 9 475 5240 www.techcomp.co.nz

### **Engineering Controls**

Local exhaust in hot processing areas.

# **Personal Protection Equipment**

Eyes	Not required but always good practice to wear eye protection.
Hands	Wear protective gloves for allergenic dermatitis sufferers.
Respiratory	Unless conditions are excessively dusty, no special precautions are required.
	In dusty areas, wearing of dust masks is recommended.

#### **Section 9 Physical and Chemical Properties**

Appearance	Extruded weatherboard of various lengths.
Odour	Not available
Odour Threshold	Not available
pH	Not available
<b>Boiling Point</b>	Not available
Melting Point	Not available
Freezing Point	Not available
Flash Point	400-460°C
Flammability	Not available
Upper and Lower	Not available
<b>Explosive Limits</b>	
Vapour Pressure	Not available
Vapour Density	Not available
Specific Gravity	1.40 - 1.50 approx.
Water Solubility	Not available
Partition Coefficient:	Not available
Auto-ignition	Not available
Temperature	
Decomposition	Not available
Temperature	
Kinematic Viscosity	Not available
Particle Characteristics	Not available

### Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Possibility of hazardous	Not known
reactions	
Conditions to Avoid	Extreme temperatures
Incompatible Materials	Strong oxidisers
<b>Hazardous Decomposition</b>	None known.
Products	

#### Section 11 **Toxicological Information**

### **Acute Effects:**

Swallowed	Not applicable.
Dermal	Not applicable.
Inhalation	Not applicable.
Eye	Not applicable.
Skin	Not applicable.

### **Chronic Effects:**

Carcinogenicity	Not applicable.	
Reproductive	Not applicable.	

Product Name: Lead-free Rigid PVC SDS Prepared by: Technical Compliance Consultants (NZ) Ltd Date of SDS: 22 June 2020

Tel: 64 9 475 5240 www.techcomp.co.nz

Toxicity	
Germ Cell	Not applicable.
Mutagenicity	
Aspiration	Not applicable.
STOT/SE	Not applicable.
STOT/RE	Not applicable.

### Section 12. Ecotoxicological Information

This product is not hazardous to the environment.

Product:	
Persistence and degradability	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	No data available

### **Section 13. Disposal Considerations**

**Disposal Method:** Product can be disposed of as recyclable material if not

contaminated with any hazardous substances. Consult with supplier

for possibility of return of unwanted product.

Precautions or methods to avoid: None known.

### Section 14 Transport Information

# This product is NOT classified as a Dangerous Good for transport in NZ; NZS 5433:2012

### Section 15 Regulatory Information

This substance is NOT classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

	Section 1	6	Other I	informa	ition
--	-----------	---	---------	---------	-------

Glossary

EC50 Median effective concentration.
EEL Environmental Exposure Limit.
EPA Environmental Protection Authority

HSNO Hazardous Substances and New Organisms.

HSW Health and Safety at Work.

LC<sub>50</sub> Lethal concentration that will kill 50% of the test organisms

inhaling or ingesting it.

LD<sub>50</sub> Lethal dose to kill 50% of test animals/organisms.

LEL Lower explosive level.

OSHA American Occupational Safety and Health Administration.

TEL Tolerable Exposure Limit.

TLV Threshold Limit Value-an exposure limit set by responsible

authority.

UEL Upper Explosive Level WES Workplace Exposure Limit

#### References:

- 1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
- 2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
- 3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
- 4. Transport of Dangerous goods on land NZS 5433:2012
- 5. HSW (Hazardous Substances) Regulations 2017

Product Name: Lead-free Rigid PVC SDS Prepared by: Technical Compliance Consultants (NZ) Ltd Date of SDS: 22 June 2020 Tel: 64 9 475 5240 www.techcomp.co.nz

#### Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the New Zealand distributor, if further information is required.

Issue Date: 22 June 2020 Review Date: 22 June 2025

Product Name: Lead-free Rigid PVC
Date of SDS: 22 June 2020

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz

Page 5